

Mi5166



Mi5166



pH & EC Pocket Tester Kit

Rating: Not Rated Yet

[Ask a question about this product](#)

Description

Mi5166 pH & EC tester kit

Specification	pH51
Range	0.0 to 14.0 pH
Resolution	0.1 pH
Accuracy	±0.1 pH
EMC Typical Deviation	±0.1 pH
Calibration	manual, 2 points through trimmer
Electrode	MA73600 (replaceable)
Environment	0 to 50°C; max RH 100%
Battery Type	3 x 1.5V; alkaline
Battery Life	more than 1500 hours of continuous use
Dimensions / Weight	165 x 30 x 30 mm / 80 g

Specification	C66
Range	0 to 10.00 mS/cm
Resolution	0.01 mS/cm
Accuracy	±2% Full Scale
Typical EMC Deviation	±2% Full Scale
Temperature Compensation	automatic from 5 to 50°C, with $\beta=2\%/^{\circ}\text{C}$
Calibration	manual, 1 point through trimmer
Probe	MA73076 (replaceable)
Environment	0 to 50°C; max RH 100%
Battery Type	3 x 1.5V; alkaline
Battery Life	approx. 250 hours of continuous use
Dimensions / Weight	165 x 30 x 30 mm / 80 g