

MW106 MAX



MW106



pH / ORP / Temperature MAX Portable Meter

Rating: Not Rated Yet
[Ask a question about this product](#)

Description

MW106 MAX pH / ORP / Temperature Professional Portable Meter

The Milwaukee **MW106 MAX** meter combines all the features of a benchtop unit into a portable, IP67 rated meter.

The instruments are provided with a series of new diagnostic features for improved pH measurement reliability:

- IP67 waterproof casing
- pH extended range: -2.00 to 20.00 pH/ -2.000 to 20.000 pH up to 5-point automatic pH calibration
- 7 standard calibration buffers (pH 1.68,4.01, 6.86, 7.01, 9.18, 10.01 and 12.45) and two custom buffers
- log space for up to 1000 records
- alphanumeric LCD displayed messages for user friendly, intuitive information / warning / error messages
- auto-off feature to preserve battery life
- internal clock and date to keep track of different
- time-dependent functions (calibration timestamp, calibration time out)
- dedicated GLP key

| Specifications | MW106 MAX |
|--------------------------|---|
| Range | pH -2.00 to 20.00 pH / -2.000 to 20.000 pH mV ±2000 mV Temp* -20.0 to 120.0 °C (-4.0 to 248.0 °F) |
| Resolution | pH 0.01 pH / 0.001 pH mV 0.1 mV Temp 0.1 °C / 0.1 °F |
| Accuracy (@25°C) | pH ±0.01 pH / ±0.002 pH mV ±1 mV Temp ±0.5°C up to 80°C, ±1°C outside / ±1°F up to 140°F, ±2°F outside |
| pH Calibration | automatic, up to 5 points calibration, 7 standard buffers available (1.68, 4.01, 6.86, 7.01, 9.18, 10.01, 12.45) and two custom buffers |
| ORP Calibration | factory calibrated |
| Temperature Compensation | automatic, from -5 to 80 °C / 23 to 178 °F |
| Probe | MA906BR/1 amplified pH/temperature probe (supplied) |
| Temperature probe | Built-in temperature probe |
| Input impedance | 10 ¹² Ohm |
| Log | Max. 1000 log records (stored in up to 100 lots) On demand, 200 logs / On stability, 200 logs / Interval logging, 1000 logs |
| PC connectivity | 1 micro USB port |
| Battery Type | 3 x 1.5V alkaline AA (included) |
| Battery Life | approx. 200 hours of use |
| Auto-off | 5, 10, 30, 60 minutes or off |
| Environment | 0 to 50 °C, 95% RH |
| Packaging dimensions | 305 x 280 x 115 mm |
| Packaging weight | 1.22 kg |

* Temperature range is limited to 80.0 °C, when using the MA906BR/1 probe

Accessories:

- **MA906BR/1** pH//Temp probe with 1 m cable
- **M10004B** pH 4.01 buffer solution 20 mL sachet (25 pcs)
- **M10006B** pH 6.86 buffer solution 20 mL sachet (25 pcs)
- **M10007B** pH 7.01 buffer solution 20 mL sachet (25 pcs)
- **M10010B** pH 10.01 buffer solution 20 mL sachet (25 pcs)
- **MA9004** pH 4.01 buffer solution, 230 mL bottle
- **MA9006** pH 6.86 buffer solution, 230 mL bottle
- **MA9007** pH 7.01 buffer solution, 230 mL bottle
- **MA9009** pH 9.18 buffer solution, 230 mL bottle
- **MA9010** pH 10.01 buffer solution, 230 mL bottle
- **MA9015** Electrode storage solution, 230 mL
- **MA9016** Electrode cleaning solution, 230 mL
- **M10000B** Electrode rinse solution, 20 mL (25 pcs)

Ordering information:

MW106 is supplied complete with MA906BR/1 pH/Temp probe, 20 mL pH 4.01 and 7.01 sachet of calibration solution, 2x20 mL sachet of electrode cleaning solutions, Micro USB cable, 9V battery, instructions, all in a rugged carrying case.